

Rev: 02



Model:

BL214 - 630-1560

Typology:

## ROUTINE MICROSCOPE

## **Description:**

Educational and laboratory microscope for routine applications.

Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Illumination	Light source type P-LED with white LED; light intensity control using a knob on left side of the frame.  LED power 3W, comparable to an halogen bulb 30-35W.  Color temperature: 6300K  LED average life time approx. 50.000h.  Voltage: external power supply 100/240Vac, 50/60Hz, output: 6 V  Max power required: 7W
Observation Modes	Brightfield
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen.  Adjustable tension of coarse focusing knob.
Stage	Double layer with mechanical sliding stage, size 125x115mm, X-Y movement range 70x30, specimen holder for one slide.  Vernier scale on the two axes, accuracy 0,1 mm.
Nosepiece	Quadruple revolving nosepiece, rotation on ball bearings.
Head	Binocular observation head, inclined 30° and rotatable 360°. Diopter adjustment on left eyepieces. Interpupillary adjustment 48-75 mm.
Eyepieces	Wide field eyepieces WF10X/18 with field number 18.
Objectives	Achromatic objectives with mechanical tube lenght 160 mm, made by following objectives:  -) Achromatic DIN 4X, A.N. 0.10, W.D. 18 mm  -) Achromatic DIN 10X, A.N. 0.25, W.D. 7 mm  -) Achromatic DIN 40X, A.N. 0.65, W.D. 0,53 mm  -) Achromatic DIN 60X, A.N. 0,85, W.D. 0,45 mm  All objectives are treated with an anti-fungus treatment.
Condenser	Abbe condenser, A.N. 1,25 precentered
Dimensions	HEIGHT: 370 mm  WIDHT: 235 mm  DEPTH: 290 mm  WEIGHT: 6,5 kg
Accessories	Instruction manual and dust cover included